

SLC LED-PANEL ECO II



ECO II is one of our most sold luminaires! With a very attractive price /quality ratio. Stable high lumen output over time (L80B10). Long lifetime and 5 year warranty. Driver is sold separately.

| Light technic | |
|-----------------------------------------------------|--------------------------------------------|
| Product ID | B_SLC8730 |
| Beam angle | Open beam/diffuse ° |
| Lamp holder | Other |
| Colour rendering index CRI | 80-89 |
| Lamp type | LED not exchangeable |
| Light sharing | Symmetric |
| With light source | Yes |
| Colour of light | White |
| Light distributor | Diffuser lens/optic/panel |
| Technical data | |
| Protection class | III |
| Colour housing | White |
| Suitable for lamp power | 36.0 - 36.0 |
| Type of control gear | LED operating device current-controlled |
| Material housing | Aluminium |
| Degree of protection (IP) | IP20 |
| Control gear included | No |
| Max. system power | 36 W |
| Rated ambient temperature according to IEC62722-2-1 | -10.0 - 40.0 °C |
| Power factor | 0.95 |
| Input | |
| Voltage type | DC |
| Nominal voltage | 8.0 - 48.0 V |
| Installation | |
| Connection type | Push-in clamp |
| Suitable for suspended mounting | Yes |
| Number of poles | 3 |
| Suitable for built-in mounting | Yes |
| Suitable for surface mounting | Yes |
| Type of wiring | Suitable for through wiring |
| Suitable for ceiling mounting | Yes |
| logistics data | |



| | |
|---------------|-----------------|
| | |
| Imported by | The Light Group |
| Brand | SLC |
| F-Pak | |
| F-pack width | 50 mm |
| F-pack height | 660 mm |
| F-pack weight | 3500 g |
| F-pack length | 700 mm |
| General data | |
| Type of grid | Matt |
| Pallet length | 1200 mm |
| M-Pak | |
| M-pack weight | 18500 g |
| M-pack height | 680 mm |
| M-pack width | 280 mm |
| M-pack length | 720 mm |
| Number | 5 |