



SLC 1-10V CONTROLLER CV 1X10A 12-36V

Mono 12-36VDC Dimmer. Mono. 1 x 10A. 96-360W. Can be dimmed with PushDim or 1-10V potmeter / shunt.

Technical data	
Product ID	S22001
Number of DALI-address	1
Dimming curve (LED)	Logarithmic
Dimming range	0-100% %
Operating temperature	-20°C ~ +45°C °C
Expected lifetime (Ta 25°C)	110000 Hours
Expected lifetime (Ta 45°C)	50000 Hours
Protection class	II
Housing	Plastic housing
Programmable	No
Degree of protection (IP)	IP20
Number of colour channels	1
Operating method	1-10 V
Dimming method	Pulse Width Modulation (PWM)
Dimming interface	1-10V
Input	
Electrical connection (Input)	L`N screw connection
Input voltage	12 - 36 V
Output	
Max total output power at 24VDC	240 W
Output type	Constant voltage (CV)
Output power per channel at 24VDC	240 W
Mono	Yes
Output power per channel	[96,360] W
Max. output current	10 mA
Max total output power	360 W
Output current per channel	[10,10] A
Number of LED Output Channels	1
Output voltage	12 - 36 V
Max output current	10 A
Installation	
Length	95 mm



21.02.2020

Subject to changes and printing errors

Height	20 mm
Width	37 mm
Model	Static
Built-in	Yes
Surface-mounted	No
Suitable for outdoor use	No
DIN rail mounting	No
logistics data	
Brand	SLC
Imported by	The Light Group
General data	
GTIN	7070938056991