

# SLC 1-10V CONTROLLER CV 4X5A 12-36V



Technical data	
Product ID	S22002
Exterior color	White
Dimming curve (LED)	Logarithmic
Dimming range	0-100% %
Operating temperature	-20°C ~ +45°C °C
Expected lifetime (Ta 25°C)	110000 Hours
Expected lifetime (Ta 45°C)	50000 Hours
Tc	75 °C
Protection class	II
Housing	Plastic housing
Programmable	No
Degree of protection (IP)	IP20
Number of colour channels	4
Operating method	1-10 V
Dimming method	Pulse Width Modulation (PWM)
Dimming interface	1-10V
Input	
Max input current	20.5 A
Strain relief	Yes
Input voltage	12 - 36 V
Output	
Max total output power at 24VDC	480 W
Output type	Constant voltage (CV)
Output power per channel at 24VDC	120 W
Mono	Yes
Output power per channel	[60,180] W
Max. output current	5 mA
Max total output power	180 W
Number of LED Output Channels	4
Output voltage	12 - 36 V
Max output current	20 A
Installation	
Length	178 mm
Height	22 mm



21.02.2020

Subject to changes and printing errors

<b>Width</b>	46 mm
<b>Model</b>	Static
<b>Built-in</b>	Yes
<b>Surface-mounted</b>	No
<b>Suitable for outdoor use</b>	No
<b>DIN rail mounting</b>	No
logistics data	
<b>Brand</b>	SLC
<b>Imported by</b>	The Light Group
General data	
<b>GTIN</b>	7070938057004