

SLC DALI DT6 CONTROLLER CV 4X5A 12-36V



Technical data	
Product ID	S23002
DALI version	DALI
DALI Type	DT6
Number of DALI-address	4
DALI-bus power consumption	2 mA
CE	Yes
Exterior color	White
Dimming curve (LED)	Logarithmic
Dimming range	0-100% %
EMC	Yes
ENEC	Yes
Flicker free	Yes
Operating temperature	-20°C ~ +45°C °C
Expected lifetime (Ta 25°C)	110000 Hours
Expected lifetime (Ta 45°C)	50000 Hours
RoHS	Yes
SELV	Yes
Tc	75 °C
Protection class	II
Housing	Plastic housing
Programmable	Yes
Degree of protection (IP)	IP20
Number of colour channels	1
Operating method	DALI
Dimming method	Pulse Width Modulation (PWM)
Dimming interface	DALI DT6
Input	
Max input current	20.5 A
Strain relief	Yes
Input voltage	12 - 36 V, [12,36] V
Output	
RGBW	Yes
Max total output power at 24VDC	480 W
Output type	Constant voltage (CV)



21.02.2020

Subject to changes and printing errors

RGB	Yes
Output power per channel at 24VDC	120 W
Mono	Yes
Output power per channel	[60,180] W
Max. output current	20 mA
Max total output power	720 W
Output current per channel	[5,5] A
Tunable White	Yes
Output voltage	12 - 36 V
Number of LED Output Channels	4
Max output current	20 A
Installation	
Length	178 mm
Height	22 mm
Width	46 mm
Model	Static
Built-in	Yes
Surface-mounted	Yes
Suitable for outdoor use	No
DIN rail mounting	No
logistics data	
Brand	SLC
General data	
GTIN	7070938057011