



SLC DALI DT6 CONTROLLER 12-36V CV 1X10A

DALI DT6 Controller with 1 channel 12-36VDC. Mono. 1 x 10A. 96-360W.

Technical data	
Product ID	S23003
DALI version	DALI2
DALI Type	DT6
Number of DALI-address	1
Operating temperature	-20°C ~ +45°C °C
Expected lifetime (Ta 25°C)	110000 Hours
Expected lifetime (Ta 45°C)	50000 Hours
Protection class	II
Housing	Plastic housing
Programmable	No
Degree of protection (IP)	IP20
Number of colour channels	1
Operating method	DALI
Dimming method	Pulse Width Modulation (PWM)
Dimming interface	DALI2 DT6
Input	
Electrical connection (Input)	L`N screw connection
Input voltage	12 - 36 V
Output	
Output type	Constant voltage (CV)
Mono	Yes
Output power per channel	[96,360] W
Max. output current	10 mA
Max total output power	360 W
Number of LED Output Channels	1
Output voltage	12 - 36 V
Installation	
Length	95 mm
Height	20 mm
Width	37 mm
Model	Static
Built-in	Yes
Surface-mounted	No



21.02.2020

Subject to changes and printing errors

Suitable for outdoor use	No
DIN rail mounting	No
logistics data	
Brand	SLC
Imported by	The Light Group
General data	
GTIN	7070938057028