



SLC DALI/AC-PUSH TO TRAILING EDGE CONTROLLER 1,5A

Perfect to control luminaries that operate with trailing edge drivers with a DALI signal. The controller converts the DALI signal to a Trailing Edge output current.



Technical data	
Product ID	S23023
Number of DALI-address	1
DALI-bus power consumption	0.5 mA
Exterior color	White
Operating temperature	-20°C ~ +45°C °C
Protection class	II
Housing	Plastic housing
Degree of protection (IP)	IP20
Number of colour channels	1
Operating method	DALI
Dimming interface	AC-Push
Input	
Electrical connection (Input)	L`N screw connection
Input voltage	100.0 - 240.0 V
Output	
Max. output current	1.5 A
Output voltage	100.0 - 240.0 V
Installation	
Length	45 mm
Height	45 mm
Width	21 mm
Model	Static
Built-in	Yes
logistics data	
Brand	SLC
D-Pak	
D-pack length	380 mm
D-pack weight	11800 g
D-pack height/diameter	280 mm
D-pack quantity	200 pcs
D-pack width	270 mm
F-Pak	

19.04.2024
Subject to changes and printing errors

F-pack width	45 mm
F-pack height	20.3 mm
F-pack weight	40 g
F-pack length	45.5 mm
M-Pak	
M-pack weight	50 g
M-pack height	55 mm
M-pack width	35 mm
M-pack length	55 mm
Number	1