

# SLC SMARTONE AC DIMMER MINI

## 200W ZIGBEE LN



Mini trailing edge dimmer based on the latest Zigbee 3.0 protocols  
 Dims from 1-100%  
 AC-Push input  
 Compatible with most smart home systems or stand alone  
 Supports TouchLink communication with Zigbee remotes and switches  
 Small size, fits in standard wall box  
 Adjustable minimum dim level



Technical data	
Product ID	S24013
CE	Yes
Exterior color	White
Operating temperature	-20°C ~ +45°C °C
Method of operation	Other
Colour	Black
Halogen free	Yes
Surface protection	Untreated
Material quality	Thermoplastic
Type of load	Universal and LED Retrofit
Material	Plastic
Light value memory	Yes
Applicable with movement sensor	Yes
Applicable with transmission button	Yes
Applicable with presence indicator	Yes
Applicable with button	Yes
Applicable with time switch/timer	Yes
Surface finishing	Matt
Dimming phase cut-off	Yes
Dimming interface	PushDim
Input	
Nominal voltage	100.0 - 240.0 V
Frequency	50.0 - 60.0 Hz
Output	
Control voltage	100.0 - 240.0 V
Installation	
Mounting method	Built-in installation
Connection type	Screwed terminal
Min. depth of built-in installation box	31 mm
Type of fastening	Other
Core cross section	0.75 - 1.5 mm²

26.04.2024

Subject to changes and printing errors

Width of device	45.5 mm
Height of device	20.3 mm
Depth of device	45 mm
logistics data	
Imported by	The Light Group
Brand	SLC
D-Pak	
D-pack length	380 mm
D-pack weight	11370 g
D-pack height/diameter	280 mm
D-pack quantity	200 pcs
D-pack width	270 mm
F-Pak	
F-pack width	45 mm
F-pack height	20.3 mm
F-pack weight	40 g
F-pack length	45.5 mm
M-Pak	
M-pack weight	50 g
M-pack height	55 mm
M-pack width	35 mm
M-pack length	55 mm
Number	1
General data	
Assembly arrangement	Basic element
Suitable for degree of protection (IP)	IP20