

SLC SMARTONE ZIGBEE CONTROLLER CV 5X4A 12-24V MONO /TW/RGB/RGBW



4 in 1 universal Zigbee LED Strip controller based on the latest Zigbee 3.0 protocol. 4 different device modes DIM, CCT, RGBW and RGB+CCT in one controller.

Technical data	
Product ID	S24018
CE	Yes
Exterior color	White
Dimming curve (LED)	Logarithmic
Dimming range	0-100% %
Flicker free	Yes
IP class	IP20
Operating temperature	-20°C ~ +45°C °C
Expected lifetime (Ta 25°C)	110000 Hours
Expected lifetime (Ta 45°C)	50000 Hours
RoHs	Yes
Tc	75 °C
Protection class	II
Housing	Plastic housing
Degree of protection (IP)	IP20
Number of colour channels	5
Operating method	Zigbee
Dimming method	Pulse Width Modulation (PWM)
Dimming interface	Zigbee
Input	
Max input current	20.5 A
Input voltage	12 - 24 V, [12,24] V
Output	
RGBW	Yes
Max total output power at 24VDC	384 W
Output type	Constant voltage (CV)
RGB	Yes
Output power per channel at 24VDC	96 W
Mono	Yes
Output power per channel	[48,96] W
Max. output current	20 A



21.10.2020

Subject to changes and printing errors

Max total output power	384 W
Output current per channel	[4,4] A
Tunable White	Yes
Number of LED Output Channels	5
Output voltage	12 - 24 V
Max output current	20 A
Installation	
Length	145 mm
Height	16 mm
Width	46.5 mm
Model	Static
Built-in	Yes
Surface-mounted	Yes
logistics data	
Brand	SLC
Imported by	The Light Group