SLC DMX RDM CONTROLLER CV 24X4A 12-24V RGBW

DMX Controller for larger applications. Can control up to 6 zones individually.



Technical data	
Product ID	S26008
CE	Yes
Exterior color	Black
Dimming curve (LED)	Logarithmic
Dimming range	0-100% %
EMC	Yes
ENEC	Yes
Flicker free	Yes
Operating temperature	-20°C ~ +45°C °C
Expected lifetime (Ta 45°C)	50000 Hours
RoHs	Yes
SELV	Yes
Tc	75 °C
Protection class	II
Housing	Metal housing
Programmable	Yes
Degree of protection (IP)	IP20
Number of colour channels	24
Operating method	DMX
Dimming method	Pulse Width Modulation (PWM)
Dimming interface	DMX
Input	
Max input current	96.5 A
Input voltage	12.0 - 24.0 V
Strain relief	No
Output	
RGBW	Yes
RGB	Yes
Output power per channel	[48.0, 96.0] W
Max. output current	96 A
Max total output power	2304 W
Output current per channel	[4.0, 4.0] A

29.03.2024

Subject to changes and printing errors

The Light Group AS, Sagmyra 2A, 4624 Kristiansand S, Norway
Tel.: +47 38 00 21 01 | E-Mail : post@tlg.no **www.tlg.no**

Output voltage	12.0 - 24.0 V
Max output current	96 A
Max total output power at 24VDC	2304 W
Output power per channel at 24VDC	96 W
Mono	Yes
Tunable White	Yes
Installation	
Length	264.5 mm
Height	42 mm
Width	83 mm
Model	Static
Surface-mounted	Yes
Suitable for outdoor use	No
logistics data	
Imported by	The Light Group
Brand	SLC
D-Pak	
D-pack length	380 mm
D-pack weight	14860 g
D-pack height/diameter	280 mm
D-pack quantity	14 pcs
D-pack width	270 mm
F-Pak	
F-pack width	83 mm
F-pack height	42 mm
F-pack weight	980 g
F-pack length	264.5 mm
M-Pak	
M-pack weight	990 g
M-pack height	130 mm
M-pack width	45 mm
M-pack length	276 mm
Number	1

The Light Group AS, Sagmyra 2A, 4624 Kristiansand S, Norway
Tel.: +47 38 00 21 01 | E-Mail : post@tlg.no **www.tlg.no**