

SLC POWER SUPPLY CV 24V 100W

PWM PUSHDIM



100W power supply with built-in PWM-dimmer. Dimmable with a simple PushDim switch. Mono.

Technical data	
Product ID	S32006
Exterior color	White
Operating temperature	-20°C ~ +45°C °C
Protection class	II
Housing	Plastic housing
Degree of protection (IP)	IP20
Suitable for constant current	No
Suitable for constant voltage	Yes
Dimming 0-10 V	No
Dimming 1-10 V	No
Dimming DALI	No
Dimming DMX	No
Dimming potentiometer (integrated)	No
Dimming LineSwitch	No
Dimming manufacturer's proprietary system	No
Dimming mains voltage modulation	No
Dimming phase cut-off	No
Dimming phase cut-on	No
Dimming programmable	No
Dimming RF	No
Dimming Sine Wave Reduction	No
Dimming Touch and Dim	No
Dimming Zigbee	No
Dimming with push-button	Yes
No dim function	No
Dimming DSI	No
Dimming interface	PushDim
Input	
Electrical connection (Input)	L`N screw connection
Power factor	0.9
Suitable for DC-voltage (primary side)	No
Output	



17.04.2024

Subject to changes and printing errors

Output power	10.0 - 100.0 W
Output voltage	24.0 - 24.0 V
Installation	
Length	244 mm
Height	32 mm
Width	64 mm
Model	Static
Suitable for outdoor use	No
logistics data	
Imported by	The Light Group
Brand	SLC