

SLC POWER SUPPLY CV 24V 100W

DALI DT6 1-4CH



Power Supply CV 24V 100W DALI DT6 1-4CH is a UL, ENEC, and TUV approved DALI 100w dimmable LEO driver with 4 channels 24VDC constant voltage output and 100-277VAC universal input.

Technical data	
Product ID	S32015
Number of DALI-address	4
Exterior color	White
Operating temperature	-20°C ~ +45°C °C
Protection class	II
Housing	Plastic housing
Degree of protection (IP)	IP20
Suitable for constant current	No
Suitable for constant voltage	Yes
Dimming 0-10 V	No
Dimming 1-10 V	No
Dimming DALI	Yes
Dimming DMX	No
Dimming potentiometer (integrated)	No
Dimming LineSwitch	No
Dimming manufacturer's proprietary system	No
Dimming mains voltage modulation	No
Dimming phase cut-off	No
Dimming phase cut-on	No
Dimming programmable	No
Dimming RF	No
Dimming Sine Wave Reduction	No
Dimming Touch and Dim	No
Dimming Zigbee	No
Dimming with push-button	No
No dim function	No
Dimming DSI	No
Dimming interface	DALI DT6
Input	
Electrical connection (Input)	L`N screw connection
Power factor	0.9
Suitable for DC-voltage (primary side)	No



23.04.2024

Subject to changes and printing errors

Output	
Output power	10.0 - 100.0 W
Output voltage	24.0 - 24.0 V
Output current	420.0 - 4200.0 mA
Installation	
Length	244 mm
Height	32 mm
Width	64 mm
Model	Static
Suitable for outdoor use	No
logistics data	
Imported by	The Light Group
Brand	SLC
D-Pak	
D-pack length	380 mm
D-pack weight	17500 g
D-pack height/diameter	280 mm
D-pack quantity	30 pcs
D-pack width	270 mm
F-Pak	
F-pack width	64 mm
F-pack height	32 mm
F-pack weight	540 g
F-pack length	244 mm
M-Pak	
M-pack weight	550 g
M-pack height	70 mm
M-pack width	40 mm
M-pack length	256 mm
Number	1