

SLC LED DRIVER DALI-2 CC DIP250-1400MA MAX 50W



Technical data	
Product ID	S32086
Number of DALI-address	1
DALI-bus power consumption	2 mA
CE	Yes
Exterior color	Black
Operating temperature	-20°C ~ +45°C °C
Protection class	II
Housing	Plastic housing
Degree of protection (IP)	IP20
Suitable for constant current	Yes
Suitable for constant voltage	No
Dimming 0-10 V	No
Dimming 1-10 V	No
Dimming DALI	Yes
Dimming DMX	No
Dimming potentiometer (integrated)	No
Dimming LineSwitch	No
Dimming manufacturer's proprietary system	No
Dimming mains voltage modulation	No
Dimming phase cut-off	No
Dimming phase cut-on	No
Dimming programmable	No
Dimming RF	No
Dimming Sine Wave Reduction	No
Dimming Touch and Dim	No
Dimming Zigbee	No
Dimming with push-button	Yes
No dim function	No
Dimming DSI	No
Dimming interface	DALI DT6
Input	
Electrical connection (Input)	L`N screw connection
Power factor	0.93
Suitable for DC-voltage (primary side)	No



25.04.2024

Subject to changes and printing errors

Output	
Output power	2.0 - 50.0 W
Output voltage	8.0 - 48.0 V
Output current	250.0 - 1400.0 mA
Installation	
Length	210 mm
Height	32 mm
Width	50 mm
Model	Dynamic
Suitable for outdoor use	No
logistics data	
Brand	SLC