

SLC LED-DRIVER CC 350MA 18W 26-52VDC TRAILING EDGE



Constant current LED-driver. Dimmable with standard trailing edge / phase cut dimmers. Comes with a 20 cm SMT plug on the secondary side for easy connection.



Technical data	
Product ID	S32110
CE	Yes
Exterior color	White
Operating temperature	-20°C ~ +45°C °C
Protection class	II
Housing	Plastic housing
Degree of protection (IP)	IP20
Suitable for constant current	Yes
Suitable for constant voltage	No
Dimming 0-10 V	No
Dimming 1-10 V	No
Dimming DALI	No
Dimming DMX	No
Dimming potentiometer (integrated)	No
Dimming LineSwitch	No
Dimming manufacturer's proprietary system	No
Dimming mains voltage modulation	No
Dimming phase cut-off	Yes
Dimming phase cut-on	Yes
Dimming programmable	No
Dimming RF	No
Dimming Sine Wave Reduction	No
Dimming Touch and Dim	No
Dimming Zigbee	No
Dimming with push-button	No
No dim function	No
Dimming DSI	No
Dimming interface	Trailing edge
Input	
Power factor	0.95
Suitable for DC-voltage (primary side)	No
Output	

26.04.2024
Subject to changes and printing errors

Output power	18.0 - 18.0 W
Output voltage	26.0 - 52.0 V
Output current	350.0 - 350.0 mA
Installation	
Length	120 mm
Height	28 mm
Width	45 mm
Model	Static
Suitable for outdoor use	No
logistics data	
Imported by	The Light Group
Brand	SLC