SLC LED-DRIVER CC 500MA 30W 30-60VDC TRAILING EDGE

Constant current LED-driver. Dimmable with standard trailing edge / phase cut dimmers. Comes with a 20 cm SMT plug on the secondary side for easy connection.



Technical data	
Product ID	S32111
Exterior color	White
Operating temperature	-20°C ~ +45°C °C
Expected lifetime (Ta 45°C)	50000 Hours
Tc	80 °C
Protection class	II
Housing	Plastic housing
Degree of protection (IP)	IP20
Suitable for constant current	Yes
Suitable for constant voltage	No
Dimming phase cut-off	Yes
Dimming phase cut-on	Yes
Dimming method	Pulse Width Modulation (PWM)
Dimming interface	Trailing edge
Input	
Power factor	0.95
Input voltage	[220.0, 240.0] V
Frequency range	[50.0, 60.0] Hz
Output	
Output power	30.0 - 30.0 W
Output type	Constant current (CC)
Output voltage	30.0 - 60.0 V
Output current	500.0 - 500.0 mA
Mono	Yes
Number of LED Output Channels	1
Installation	
Length	142 mm
Height	24 mm
Width	50 mm
Model	Static
logistics data	
Brand	SLC

29.03.2024

Subject to changes and printing errors

The Light Group AS, Sagmyra 2A, 4624 Kristiansand S, Norway
Tel.: +47 38 00 21 01 | E-Mail : post@tlg.no **www.tlg.no**

The Light Group AS, Sagmyra 2A, 4624 Kristiansand S, Norway
Tel.: +47 38 00 21 01 | E-Mail : post@tlg.no **www.tlg.no**