



SLC DALI DT8 RGB/RGBW WALL PANEL TOUCH MCU/SLAVE

Adjust the color and light level of a channel or broadcast. DALI master for use without central DALI bus. Can also be set up as a slave with PSU.

Technical data	
Product ID	S52033
DALI bus output power	100 mA
Number of DALI-address	1
DALI-bus power consumption	15 mA
Operating temperature	0°C ~ +40°C °C
Protection class	II
Housing	Other
Programmable	Yes
Degree of protection (IP)	IP20
Number of colour channels	4
Operating method	DALI
Dimming interface	DALI DT8
Input	
Electrical connection (Input)	L`N screw connection
Input voltage	100.0 - 240.0 V
Installation	
Length	86 mm
Height	29 mm
Width	86 mm
Model	Static
Built-in	Yes
Surface-mounted	Yes
Suitable for outdoor use	No
DIN rail mounting	No
logistics data	
Imported by	The Light Group
Brand	SLC
D-Pak	
D-pack length	380 mm
D-pack weight	7840 g
D-pack height/diameter	280 mm
D-pack quantity	36 pcs



25.04.2024

Subject to changes and printing errors

D-pack width	270 mm
F-Pak	
F-pack width	86 mm
F-pack height	41 mm
F-pack weight	180 g
F-pack length	86 mm
M-Pak	
M-pack weight	190 g
M-pack height	100 mm
M-pack width	53 mm
M-pack length	110 mm
Number	1