



SLC LED-PANEL R600 BASE RGB

46W OP



Light technic	
Product ID	SLC8710
Beam angle	Extreme wide beam >80° °
Colour rendering index CRI	80-89
Lamp type	LED not exchangeable
Light outlet	Direct
Light sharing	Symmetric
With light source	Yes
Colour of light	RGB
Rated life time L70/B50 at 25 °C	50000 Hours
Light distributor	Diffuser lens/optic/panel
Energy efficiency class of the built-in lamp	A++, A+, A (LED)
Technical data	
Protection class	II
Colour housing	White
Suitable for lamp power	46 - 46
Type of control gear	LED operating device current-controlled
Material housing	Aluminium
Material cover	Plastic, opal
Degree of protection (IP)	IP20
Control gear included	No
Max. system power	46 W
Rated ambient temperature according to IEC62722-2-1	-10 - 40 °C
Dimming depending on control gear	Yes
Power factor	0.9
Input	
Nominal voltage	24 - 24 V
Voltage type	AC
Installation	
Height/depth	12 mm
Built-in width	600 mm
Built-in height/depth	12 mm
Length	600 mm

05.07.2020

Subject to changes and printing errors

Built-in length	600 mm
Width	600 mm
Connection type	Plug clamp
Suitable for suspended mounting	Yes
Number of poles	3
Suitable for built-in mounting	Yes
Suitable for surface mounting	Yes
Type of wiring	Suitable for through wiring
Suitable for ceiling mounting	Yes
logistics data	
Brand	SLC
Imported by	The Light Group
General data	
GTIN	7070938059589
Type of grid	None