



# SLC LOGIQ LED DRIVER CC MULTI 75W 4CH

LogiQ multi CC dimmable 4 channel driver for LED luminaries. Works with multiple control modules: DALI (DT6/DT8), DMX/RDM, RF, 1-10V, ZigBee, Z-Wave (see accessories or plugin modules). Mono, TW, RGB and RGBW

Technical data	
Product ID	S37002
CE	Yes
Exterior color	White
EMC	Yes
ENEC	Yes
Flicker free	Yes
Operating temperature	-20°C ~ +45°C °C
Expected lifetime (Ta 25°C)	110000 Hours
Expected lifetime (Ta 45°C)	50000 Hours
Over temperature protection	Yes
Over voltage protection	Yes
RoHs	Yes
SELV	Yes
Short circuit protection	Yes
Tc	85 °C
Protection class	II
Housing	Plastic housing
Degree of protection (IP)	IP20
Suitable for constant current	Yes
Dimming method	Pulse Width Modulation (PWM)
Input	
Electrical connection (Input)	L`N screw connection
Power factor	0.96
Frequency range	[50,60] Hz
Inrush Current	0.91 A
Input voltage	[100,277] V
Leakage Current	0.5 mA
Output	
Output current	250 - 1500 mA
RGBW	Yes
Output power	1 - 75 W
DIP-switch	Yes



29.10.2020

Subject to changes and printing errors

<b>Output type</b>	Constant current (CC)
<b>RGB</b>	Yes
<b>Mono</b>	Yes
<b>Max total output power</b>	75 W
<b>Tunable White</b>	Yes
<b>Number of LED Output Channels</b>	4
<b>Output voltage</b>	6 - 48 V
<b>Max output current</b>	1.5 A
<b>Installation</b>	
<b>Length</b>	174 mm
<b>Height</b>	38 mm
<b>Width</b>	94 mm
<b>Model</b>	Dynamic
<b>logistics data</b>	
<b>Brand</b>	SLC