



SLC LOGIQ LED DRIVER CV 12VDC 50W 2CH

LogiQ Constant Voltage 12V dimmable 2 channel driver for LED luminaries. Works with multiple control modules: DALI (DT6/DT8), DMX /RDM, RF, 1-10V, ZigBee, Z-Wave (see accessories or plugin modules).

Technical data	
Product ID	S37011
CE	Yes
Exterior color	White
EMC	Yes
ENEC	Yes
Flicker free	Yes
Operating temperature	-20°C ~ +45°C °C
Expected lifetime (Ta 25°C)	110000 Hours
Expected lifetime (Ta 45°C)	50000 Hours
Over temperature protection	Yes
Over voltage protection	Yes
RoHs	Yes
SELV	Yes
Short circuit protection	Yes
Tc	85 °C
Protection class	II
Housing	Plastic housing
Degree of protection (IP)	IP20
Suitable for constant voltage	Yes
Dimming method	Pulse Width Modulation (PWM)
Input	
Electrical connection (Input)	L`N screw connection
Power factor	0.95
Strain relief	Yes
Frequency range	[50,60] Hz
Inrush Current	0.6 A
Input voltage	[100,277] V
Leakage Current	0.5 mA
Output	
Output power	1 - 50 W
Electrical connection (Out)	L`N screw connection
Output type	Constant voltage (CV)



29.10.2020

Subject to changes and printing errors

Mono	Yes
Max total output power	50 W
Number of LED Output Channels	2
Output voltage	12 - 12 V
Max output current	4.16 A
Installation	
Length	158.7 mm
Height	38 mm
Width	844 mm
Model	Dynamic
logistics data	
Brand	SLC