



# SLC LOGIQ LED DRIVER CV 24VDC 60W 2CH

LogiQ Constant Voltage 24V dimmable 2 channel driver for LED luminaries. Works with multiple control modules: DALI (DT6/DT8), DMX /RDM, RF, 1-10V, ZigBee, Z-Wave (see accessories or plugin modules).

Technical data	
Product ID	S37021
CE	Yes
Exterior color	White
EMC	Yes
ENEC	Yes
Flicker free	Yes
Operating temperature	-20°C ~ +45°C °C
Expected lifetime (Ta 25°C)	110000 Hours
Expected lifetime (Ta 45°C)	50000 Hours
Over temperature protection	Yes
Over voltage protection	Yes
RoHs	Yes
SELV	Yes
Short circuit protection	Yes
Tc	85 °C
Protection class	II
Housing	Plastic housing
Degree of protection (IP)	IP20
Suitable for constant voltage	Yes
Dimming method	Pulse Width Modulation (PWM)
Input	
Electrical connection (Input)	L`N screw connection
Power factor	0.95
Strain relief	Yes
Frequency range	[50,60] Hz
Inrush Current	0.71 A
Input voltage	[100,277] V
Leakage Current	0.5 mA
Output	
Max total output power at 24VDC	60 W
Output power	1 - 60 W
Electrical connection (Out)	L`N quick connection



29.10.2020

Subject to changes and printing errors

<b>Output type</b>	Constant voltage (CV)
<b>Output power per channel at 24VDC</b>	60 W
<b>Mono</b>	Yes
<b>Output power per channel</b>	[1,60] W
<b>Max total output power</b>	60 W
<b>Number of LED Output Channels</b>	2
<b>Output voltage</b>	24 - 24 V
<b>Max output current</b>	2.5 A
<b>Installation</b>	
<b>Length</b>	159 mm
<b>Height</b>	38 mm
<b>Width</b>	84 mm
<b>Model</b>	Dynamic
<b>logistics data</b>	
<b>Brand</b>	SLC