CE

SLC FOCUS R565 BASE 3797LM 3000K CRI80 30W

Innovative and modern design. Developed towards high efficacy (140lm /W), long lifetime and low glare rating (UGR<16). The FOCUS panel is an all-around panel, combined with a wide range of drivers and output packages. Can be recessed or surface mounted. Perfect choice for projects aspiring to be carried out with sustainability focus, efficiency and reduced carbon footprint (BREEAM etc.).

Light technic	
Product ID	SLC8760
Beam angle	Open beam/diffuse °
MacAdam (SDCM)	3
Glare (UGR)	UGR<16
Colour rendering index CRI	80-89
Lamp type	LED not exchangeable
Light outlet	Direct
Light sharing	Symmetric
With light source	Yes
Colour temperature	3000.0 - 3000.0 K
Rated luminous flux according to IEC 62722-2-1	3797 lm
Colour of light	White
Light distributor	Focal lens
Luminaire efficacy	126.5 lm/W
Technical data	
CE	Yes
Protection class	III
Colour housing	White
Suitable for lamp power	27.0 - 36.0
Type of control gear	LED operating device current-controlled
Material housing	Aluminium
Material cover	Plastic, transparent
Impact strength	IK08
Degree of protection (IP)	IP40
Covering of the luminaire with thermally insulating material possible	No
Control gear included	No
Max. system power	36 W
Rated ambient temperature according to IEC62722-2-1	-10.0 - 45.0 °C



Filament test according to IEC 60695-2-11	750 °C - 30 s
Power factor	0.9
Input	
Voltage type	DC
Nominal voltage	33.0 - 38.0 V
Installation	
Height/depth	36 mm
Built-in width	595 mm
Built-in height/depth	36 mm
Length	600 mm
Built-in length	595 mm
Width	600 mm
Conductor cross section	0.75 mm2
Connection type	Push-in clamp
Suitable for suspended mounting	No
Number of poles	2
Suitable for built-in mounting	Yes
Suitable for surface mounting	Yes
Type of wiring	Suitable for through wiring
Suitable for ceiling mounting	Yes
Suitable for ceiling mounting logistics data	Yes
	Yes The Light Group
logistics data	
logistics data	The Light Group
logistics data Imported by Brand	The Light Group
logistics data Imported by Brand F-Pak	The Light Group
logistics data Imported by Brand F-Pak F-pack width	The Light Group SLC 62 mm
logistics data Imported by Brand F-Pak F-pack width F-pack height	The Light Group SLC 62 mm 675 mm
logistics data Imported by Brand F-Pak F-pack width F-pack height F-pack length	The Light Group SLC 62 mm 675 mm
Imported by Brand F-Pak F-pack width F-pack height F-pack length General data	The Light Group SLC 62 mm 675 mm 645 mm
Imported by Brand F-Pak F-pack width F-pack height F-pack length General data Type of grid	The Light Group SLC 62 mm 675 mm 645 mm
logistics data Imported by Brand F-Pak F-pack width F-pack height F-pack length General data Type of grid M-Pak	The Light Group SLC 62 mm 675 mm 645 mm
logistics data Imported by Brand F-Pak F-pack width F-pack height F-pack length General data Type of grid M-Pak M-pack height	The Light Group SLC 62 mm 675 mm 645 mm None