



# SLC 1-10V CONTROLLER CV 4CH 4X5A

Controller with 4 channel 0/1-10V signal Input and 4 channels PWM Output. Receives standard 0/1-10V dimming signal. 0-100% dimming range via logarithmic characteristic, perfect for human's vision.

Technical data	
Product ID	S22004
CE	Yes
Exterior color	White
Dimming curve (LED)	Logarithmic
Dimming range	0-100% %
ENEC	Yes
Flicker free	Yes
Operating temperature	-20°C ~ +45°C °C
Expected lifetime (Ta 25°C)	100000 Hours
Expected lifetime (Ta 45°C)	50000 Hours
RoHs	Yes
Tc	75 °C
Protection class	II
Housing	Plastic housing
Degree of protection (IP)	IP20
Number of colour channels	4
Operating method	1-10 V
Dimming method	Pulse Width Modulation (PWM)
Dimming interface	1-10V
Input	
Input voltage	12 - 36 V
Output	
Max total output power at 24VDC	480 W
Output type	Constant voltage (CV)
Output power per channel at 24VDC	120 W
Mono	Yes
Output power per channel	[60,180] W
Max. output current	20 mA
Max total output power	720 W
Output current per channel	[5,5] A
Output voltage	12 - 36 V
Max output current	20 A



21.02.2020

Subject to changes and printing errors

Installation	
Length	178 mm
Height	22 mm
Width	46 mm
Model	Static
Surface-mounted	Yes
logistics data	
Brand	SLC
Imported by	The Light Group