

SLC ONE360 DOWNLIGHT R68-83 DIM TO WARM TED



One 360° is "a jack of all trades" downlight for all types of installations. If you could only choose One downlight, the One360° would be your best choice. You can't go wrong with a semi-recessed high end LED chip together with tilt/ rotate, iso safe design, flexible cut-out hole and low installation depth. The One 360° thrives just as good in a cornice in the Norwegian mountains as in a warm and cosy living room.



| Light technic | |
|---|--|
| Product ID | B_SLC1141 |
| Beam angle | 36 °, Medium beam 21-40° ° |
| Expected lifetime | 50 000 |
| Light reduction | L80B10 |
| MacAdam (SDCM) | 3 |
| Reflector | High-gloss |
| Colour rendering index CRI | 90-100 |
| Lamp type | LED not exchangeable |
| Light outlet | Direct |
| Light sharing | Symmetric |
| With light source | Yes |
| Colour of light | White |
| Colour consistency (McAdam ellipse) | SDCM3 |
| Light distributor | Reflector |
| Luminaire efficacy | 75 lm/W |
| Technical data | |
| CE | Yes |
| IP class | IP44 |
| Operating temperature | -10°C ~ +45°C °C |
| Protection class | II |
| Surface protection | Powder coating |
| Type of control gear | LED operating device current-controlled |
| Material housing | Aluminium |
| Material cover | Plastic, transparent |
| Degree of protection (IP) | IP44 |
| Control gear included | Yes |
| Max. system power | 8 W |
| Adjustability | Rotating and swivelling |
| Rated ambient temperature according to IEC62722-2-1 | -10.0 - 45.0 °C |

26.04.2024
Subject to changes and printing errors

| | |
|---|-----------------------------|
| Dimming phase cut-off | Yes |
| Power factor | 0.9 |
| Dimming interface | Trailing edge |
| Input | |
| Electrical connection (Input) | L`L`N`N quick connection |
| Voltage type | AC |
| Nominal voltage | 220.0 - 240.0 V |
| Power factor | 0.9 |
| Installation | |
| Built-in width | 67 mm |
| Height | 45.4 mm |
| Built-in height/depth | 46 mm |
| Length | 90 mm |
| Width | 90 mm |
| Can be installed directly into the insulation | Yes |
| Outer diameter | 90 mm |
| Conductor cross section | 0.35 mm ² |
| Connection type | Push-in clamp |
| Suitable for suspended mounting | No |
| Number of poles | 3 |
| Suitable for built-in mounting | Yes |
| Connectable conductor cross section | 0.75 - 2.5 mm ² |
| Type of wiring | Suitable for through wiring |
| Suitable for ceiling mounting | Yes |
| logistics data | |
| Imported by | The Light Group |
| Brand | SLC |
| F-Pak | |
| F-pack width | 112 mm |
| F-pack height | 100 mm |
| F-pack weight | 365 g |
| F-pack length | 100 mm |
| General data | |
| Pallet length | 1200 mm |
| Rated power | 8 W |
| M-Pak | |
| M-pack length | 535 mm |
| Number | 50 |
| M-pack weight | 19200 g |

26.04.2024
Subject to changes and printing errors

| | |
|---------------|--------|
| M-pack height | 520 mm |
| M-pack width | 232 mm |