

SLC LED STRIP UL ICC 60 20M 10MM

4,32W 340LM 4000K CRI80 IP67



LED strip for longer distances, up to 20 meters per connection. Suitable for visual decorative effects and for highlighting details. Particularly suitable where long lengths are needed, such as handrails, walls etc. Constant current technology protects each LED chip against voltage drop and provides a more even light from connection to end point over longer lengths. With double-sided 3M tape, the strip is versatile and easy to install.



Light technic	
Product ID	S10034
Beam angle	120 °, 120
Colour rendering index (CRI /Ra)	80
Expected lifetime	60 000
Number of LED`s per meter	60
Light reduction	L80B10
Efficacy	79 lm/W
Lumens pr. meter	340 lm
MacAdam (SDCM)	3
Colour rendering index CRI	80-89
Lamp type	LED not exchangeable
Lamp power per meter	4.3 W/m
Number of nodes per meter	60 LED`s
Colour temperature	4000.0 - 4000.0 K
Colour of light	White
Luminous flux per meter	340 lm/m
Rated life time L70/B50 at 25 ° C	120000 Hours
Lamp power per foot	1.29 W
Luminaire efficacy	79 lm/W
Number of nodes per foot	18
Technical data	
CE	Yes
Exterior color	White
Cutting point, every	100 mm
Dimmable	Yes
IP class	IP67
LED-Strip length	20 m
Max length per connection:	20 meter m
Operating temperature	-10°C ~ +45°C °C

25.04.2024
Subject to changes and printing errors

Rated power per meter	4.3 W/m
Protection class	II
Type of control gear	LED operating device voltage-controlled
Suitable for dimmer	Yes
Degree of protection (IP)	IP67
Lamp voltage	24.0 - 24.0 V
Max. system power	43 W
Technology	Constant voltage (CV)
Input	
Electrical connection (Input)	2 meter wire in each end
Voltage type	DC
Installation	
Length of particular segments	100 mm
Height/depth	4 mm
Height	4 mm
Length	20000 mm
Width	10 mm, 10 mm
Mounting method	Surface mounting/recessed mounting
Model	Strip
Conductor cross section	0.35 mm ²
Connection type	Solder
Self-adhesive	Yes
Number of poles	2
With protective cover	Yes
With connection set	No
With end piece	No
Type of wiring	Ending
logistics data	
Imported by	The Light Group
Brand	SLC
D-Pak	
D-pack length	360 mm
D-pack weight	15000 g
D-pack height/diameter	380 mm
D-pack quantity	5 pcs
D-pack width	320 mm
F-Pak	
F-pack width	385 mm
F-pack height	18 mm

25.04.2024
Subject to changes and printing errors

F-pack weight	2950 g
F-pack length	395 mm
EPREL Data	
EPREL Energy Class	G