

# LED STRIP 230V 72 1-50M 15MM 14W

## 1470LM 840 IP65

LED strip that connects directly to 230V and therefore does not need a driver. Time-saving and efficient solution. \*Sold to measure. When ordering, state the desired length: 167 mm intervals, 50m max length.



| Light technic                 |                                    |
|-------------------------------|------------------------------------|
| Product ID                    | SM17024                            |
| MacAdam (SDCM)                | 3                                  |
| Beam angle                    | 110                                |
| Colour rendering index CRI    | 80-89                              |
| Lamp type                     | LED not exchangeable               |
| Lamp power per meter          | 14 W/m                             |
| Number of nodes per meter     | 72 LED`s                           |
| Colour temperature            | 4000.0 - 4000.0 K                  |
| Colour of light               | White                              |
| Luminous flux per meter       | 1470 lm/m                          |
| Technical data                |                                    |
| CE                            | Yes                                |
| IP class                      | IP65                               |
| LED-Strip length              | 1 m                                |
| Max length per connection:    | 50 meter m                         |
| Protection class              | II                                 |
| Type of control gear          | Not required                       |
| Degree of protection (IP)     | IP65                               |
| Lamp voltage                  | 230.0 - 230.0 V                    |
| Max. system power             | 700 W                              |
| Input                         |                                    |
| Voltage type                  | AC                                 |
| Installation                  |                                    |
| Length of particular segments | 167 mm                             |
| Height/depth                  | 6.5 mm                             |
| Length                        | 167 mm                             |
| Width                         | 15 mm                              |
| Mounting method               | Surface mounting/recessed mounting |
| Model                         | Strip                              |
| Conductor cross section       | 0.75 mm <sup>2</sup>               |
| Number of poles               | 2                                  |
| With protective cover         | Yes                                |

24.04.2024  
Subject to changes and printing errors

|                |                 |
|----------------|-----------------|
| With end piece | Yes             |
| Type of wiring | Ending          |
| logistics data |                 |
| Brand          | SLC             |
| Imported by    | The Light Group |