

SLC LED STRIP HE CV 160 5M 10MM

19,2W 2900LM 4000K CRI80 IP20



Professional LED strip with high light output per meter and high efficiency.
Suitable for projects where the amount of light is important.

Light technic	
Product ID	S13068
MacAdam (SDCM)	3
Beam angle	120
Colour rendering index CRI	80-89
Lamp type	LED not exchangeable
Lamp power per meter	19.2 W/m
Number of nodes per meter	160 LED`s
Colour temperature	4000.0 - 4000.0 K
Colour of light	White
Luminous flux per meter	2900 lm/m
Luminaire efficacy	151 lm/W
Technical data	
CE	Yes
IP class	IP20
LED-Strip length	5 m
Max length per connection:	5 meter m
Protection class	II
Type of control gear	LED operating device voltage-controlled
Suitable for dimmer	Yes
Degree of protection (IP)	IP20
Lamp voltage	24.0 - 24.0 V
Max. system power	96 W
Power factor	0.95
Input	
Voltage type	DC
Installation	
Length of particular segments	50 mm
Height/depth	2 mm
Length	5000 mm
Width	10 mm
Mounting method	Surface mounting/recessed mounting



Model	Strip
Conductor cross section	0.35 mm2
Number of poles	2
With connection set	Yes
Type of wiring	Ending
logistics data	
Imported by	The Light Group
Brand	SLC
D-Pak	
D-pack length	550 mm
D-pack weight	17600 g
D-pack height/diameter	450 mm
D-pack quantity	100 pcs
D-pack width	290 mm
F-Pak	
F-pack width	190 mm
F-pack height	12 mm
F-pack weight	170 g
F-pack length	205 mm
M-Pak	
M-pack weight	4400 g
M-pack height	250 mm
M-pack width	220 mm
M-pack length	260 mm
Number	25
EPREL Data	
EPREL Energy Class	E