

SLC LED STRIPS FULL SPECTRUM

9,6W 5 METER CRI>98



Full spectrum color rendering, designed for accurate color rendering; CRI>98. 120 LEDs per meter make it easy to create an even line of light in most installations. With double-sided 3M 300LSE tape, the strip is versatile and easy to install. Should be laid in profile for cooling to ensure longevity.

Light technic	
Product ID	B_S11200
MacAdam (SDCM)	3
Beam angle	120
Colour rendering index CRI	90-100
Lamp type	LED not exchangeable
Lamp power per meter	9.6 W/m
Number of nodes per meter	120 LED`s
Colour of light	White
Technical data	
CE	Yes
Dimmable	Yes
LED-Strip length	5 m
Max length per connection:	5 meter m
Operating temperature	-20°C ~ +45°C °C
Protection class	II
Type of control gear	LED operating device voltage-controlled
Suitable for dimmer	Yes
Degree of protection (IP)	IP20
Lamp voltage	24.0 - 24.0 V
Max. system power	48 W
Power factor	0.95
Technology	Constant voltage (CV)
Input	
Voltage type	DC
Installation	
Length of particular segments	50 mm
Height/depth	2 mm
Length	5000 mm
Width	10 mm
Mounting method	Surface mounting/recessed mounting



Model	Strip
Conductor cross section	0.35 mm2
Self-adhesive	Yes
Number of poles	2
Type of wiring	Ending
logistics data	
Imported by	The Light Group
Brand	SLC