SLC LED STRIP TW 196 5M 10MM 14,4 W 1683LM 2200-6500K CRI80 IP54

Tunable White technology is the solution when one shade of white is not enough. Two-color LED strip with the colors 2200K and 6500K that together provide a dynamic white light spectrum. This changes the overall feel of the room - from the ultra-warm 2200K to the highly efficient 6500K. Set the light color in the room according to the desired mood and with our TW controller you get a simple and user-friendly stand-alone solution that fits in all installations.



Light technic	
Product ID	S14037
MacAdam (SDCM)	3
Beam angle	120
Colour rendering index CRI	80-89
Lamp type	LED not exchangeable
Lamp power per meter	14.4 W/m
Number of nodes per meter	196 LED`s
Colour temperature	2200.0 - 6500.0 K
Colour of light	White
Luminous flux per meter	1683 lm/m
Luminaire efficacy	116.9 lm/W
Technical data	
CE	Yes
Exterior color	White
Dimmable	Yes
IP class	IP54
LED-Strip length	5 m
Max length per connection:	5 meter m
Protection class	II
Type of control gear	LED operating device voltage-controlled
Suitable for dimmer	Yes
Degree of protection (IP)	IP54
Lamp voltage	24.0 - 24.0 V
Max. system power	72 W
Technology	Constant voltage (CV)
Input	
Electrical connection (Input)	2 meter wire in each end
Voltage type	DC
Installation	

28.03.2024

Subject to changes and printing errors

Length of particular segments	71.42 mm
Height/depth	1 mm
Length	5000 mm
Width	10 mm
Mounting method	Surface mounting/recessed mounting
Model	Strip
Conductor cross section	0.35 mm2
Self-adhesive	Yes
Number of poles	3
With connection set	Yes
Type of wiring	Ending
	logistics data
Imported by	The Light Group
Brand	SLC
	D-Pak
D-pack length	550 mm
D-pack weight	14400 g
D-pack height/diameter	450 mm
D-pack quantity	40 pcs
D-pack width	290 mm
	F-Pak
F-pack width	260 mm
F-pack height	18 mm
F-pack weight	330 g
F-pack length	270 mm
	M-Pak
M-pack weight	3600 g
M-pack height	250 mm
M-pack width	220 mm
M-pack length	260 mm
Number	10
	EPREL Data
EPREL Energy Class	F

The Light Group AS, Sagmyra 2A, 4624 Kristiansand S, Norway
Tel.: +47 38 00 21 01 | E-Mail : post@tlg.no **www.tlg.no**