

SLC LED STRIP TW 196 5M 10MM 14,4 W 1683LM 2200-6500K CRI80 IP20



Tunable White technology is the solution when one shade of white is not enough. Two-color LED strip with the colors 2200K and 6500K that together provide a dynamic white light spectrum. This changes the overall feel of the room - from the ultra-warm 2200K to the highly efficient 6500K. Set the light color in the room according to the desired mood and with our TW controller you get a simple and user-friendly stand-alone solution that fits in all installations.



Light technic	
Product ID	S14036
MacAdam (SDCM)	3
Beam angle	120
Colour rendering index CRI	80-89
Lamp type	LED not exchangeable
Lamp power per meter	14.4 W/m
Number of nodes per meter	196 LED`s
Colour temperature	2200.0 - 6500.0 K
Colour of light	White
Luminous flux per meter	1683 lm/m
Luminaire efficacy	116.9 lm/W
Technical data	
CE	Yes
Exterior color	White
Dimmable	Yes
IP class	IP20
LED-Strip length	5 m
Max length per connection:	5 meter m
Protection class	II
Type of control gear	LED operating device voltage-controlled
Suitable for dimmer	Yes
Degree of protection (IP)	IP20
Lamp voltage	24.0 - 24.0 V
Max. system power	72 W
Technology	Constant voltage (CV)
Input	
Electrical connection (Input)	2 meter wire in each end
Voltage type	DC
Installation	

27.04.2024
Subject to changes and printing errors

Length of particular segments	71.42 mm
Height/depth	1 mm
Length	5000 mm
Width	10 mm
Mounting method	Surface mounting/recessed mounting
Model	Strip
Conductor cross section	0.35 mm ²
Self-adhesive	Yes
Number of poles	3
With connection set	Yes
Type of wiring	Ending
logistics data	
Imported by	The Light Group
Brand	SLC
D-Pak	
D-pack length	550 mm
D-pack weight	17600 g
D-pack height/diameter	450 mm
D-pack quantity	100 pcs
D-pack width	290 mm
F-Pak	
F-pack width	190 mm
F-pack height	12 mm
F-pack weight	170 g
F-pack length	205 mm
M-Pak	
M-pack weight	4400 g
M-pack height	250 mm
M-pack width	220 mm
M-pack length	260 mm
Number	25
EPREL Data	
EPREL Energy Class	E