

SLC LED STRIP TW CV 196 5M 10MM

20W 2200LM 2200-6500K CRI80 IP20



• Tunable White technology is the solution in cases where fixed colour temperature is not enough• Two LED`s with 2200K and 6500K that together create a dynamic light spectrum• This totally changes the ambience of the room - from the ultra-warm and cosy 2200K to the high-efficiency 6500K

Light technic	
Product ID	S14035
MacAdam (SDCM)	3
Beam angle	120
Colour rendering index CRI	80-89
Lamp type	LED not exchangeable
Lamp power per meter	20 W/m
Number of nodes per meter	196 LED`s
Colour temperature	2200.0 - 6500.0 K
Colour of light	White
Luminous flux per meter	2200 lm/m
Luminaire efficacy	110 lm/W
Technical data	
CE	Yes
IP class	IP20
LED-Strip length	5 m
Max length per connection:	5 meter m
Protection class	II
Type of control gear	LED operating device voltage-controlled
Suitable for dimmer	Yes
Degree of protection (IP)	IP20
Lamp voltage	24.0 - 24.0 V
Max. system power	100 W
Input	
Electrical connection (Input)	2 meter wire in each end
Voltage type	DC
Installation	
Length of particular segments	71.4 mm
Height/depth	2 mm
Length	5000 mm



Width	10 mm
Mounting method	Surface mounting/recessed mounting
Model	Strip
Conductor cross section	0.35 mm ²
Connection type	Other
Number of poles	3
With connection set	Yes
Type of wiring	Ending
	D-Pak
D-pack length	550 mm
D-pack weight	17600 g
D-pack height/diameter	450 mm
D-pack quantity	100 pcs
D-pack width	290 mm
	F-Pak
F-pack width	190 mm
F-pack height	12 mm
F-pack weight	170 g
F-pack length	205 mm
	M-Pak
M-pack weight	4400 g
M-pack height	250 mm
M-pack width	220 mm
M-pack length	260 mm
Number	25
	EPREL Data
EPREL Energy Class	F