


SLC LED STRIP RGB CV 120 5M

10MM 21,6W 650LM IP20



• High power RGB strip for extra powerful light output and density between diodes• This combination gives a smoother line and higher quality of visible light in the finished product

Light technic	
Product ID	S14046
Beam angle	120
Lamp power per meter	21.6 W/m
Number of nodes per meter	120 LED`s
Colour of light	RGB
Luminous flux per meter	650 lm/m
Luminaire efficacy	30 lm/W
Technical data	
CE	Yes
Dimmable	Yes
IP class	IP20
LED-Strip length	5 m
Max length per connection:	5 meter m
Operating temperature	-10°C ~ +45°C °C
Protection class	II
Type of control gear	LED operating device voltage-controlled
Suitable for dimmer	Yes
Degree of protection (IP)	IP20
Lamp voltage	24.0 - 24.0 V
Max. system power	108 W
Input	
Electrical connection (Input)	2 meter wire in each end
Voltage type	DC
Installation	
Length of particular segments	50 mm
Height/depth	2 mm
Length	5000 mm
Width	10 mm
Mounting method	Surface mounting/recessed mounting
Model	Strip
Conductor cross section	0.35 mm ²



Connection type	Other
Number of poles	4
With connection set	Yes
Type of wiring	Ending
logistics data	
Imported by	The Light Group
Brand	SLC
D-Pak	
D-pack length	550 mm
D-pack weight	17600 g
D-pack height/diameter	450 mm
D-pack quantity	100 pcs
D-pack width	290 mm
F-Pak	
F-pack width	190 mm
F-pack height	12 mm
F-pack weight	170 g
F-pack length	205 mm
M-Pak	
M-pack weight	4400 g
M-pack height	250 mm
M-pack width	220 mm
M-pack length	260 mm
Number	25