



# SLC LED STRIP DIGITAL RGBW SPI

## 60 5M 10MM 19W 730LM 830 IP20

Programmable digital LED strip. Programmed and controlled using SPI signal.

Light technic	
Product ID	S14047
MacAdam (SDCM)	5
Beam angle	120
Colour rendering index CRI	80-89
Lamp type	LED not exchangeable
Lamp power per meter	19 W/m
Number of nodes per meter	60 LED`s
Colour temperature	3000.0 - 3000.0 K
Colour of light	RGBW
Luminous flux per meter	730 lm/m
Rated life time L70/B50 at 25 °C	36000 Hours
Technical data	
CE	Yes
EMC	Yes
LED-Strip length	5 m
Max length per connection:	5 meter m
Operating temperature	-20°C ~ +45°C °C
RoHs	Yes
Protection class	II
Type of control gear	LED operating device voltage-controlled
Degree of protection (IP)	IP20
Lamp voltage	24.0 - 24.0 V
Max. system power	95 W
	Input
Electrical connection (Input)	2 meter wire in each end
Voltage type	DC
Installation	
Length of particular segments	100 mm
Height/depth	2 mm
Length	5000 mm
Width	10 mm



19.09.2021

Subject to changes and printing errors

<b>Mounting method</b>	Surface mounting/recessed mounting
<b>Model</b>	Strip
<b>Conductor cross section</b>	0.35 mm <sup>2</sup>
<b>Number of poles</b>	3
<b>With connection set</b>	Yes
<b>With end piece</b>	No
<b>Type of wiring</b>	Ending
	logistics data
<b>Brand</b>	SLC
<b>Imported by</b>	The Light Group