

SLC LED-PANEL THINK R600X600

TUNABLE WHITE TW



LED-panel developed to meet increased standards. High efficacy values (130lm/W). Tuning between 2700-6500K allows you to create a comfortable office or classroom environments using Human Centric Lighting.



Light technic	
Product ID	SLC8752
Beam angle	Open beam/diffuse °
Colour rendering index CRI	80-89
Lamp type	LED not exchangeable
Light sharing	Symmetric
Colour temperature	2700.0 - 6500.0 K
Colour of light	White
Light distributor	Diffuser lens/optic/panel
Luminaire efficacy	130 lm/W
Technical data	
Protection class	III
Colour housing	White
Suitable for lamp power	27.0 - 36.0
Type of control gear	LED operating device current-controlled
Material housing	Aluminium
Material cover	Plastic, opal
Degree of protection (IP)	IP20
Control gear included	No
Max. system power	36 W
Rated ambient temperature according to IEC62722-2-1	-10.0 - 45.0 °C
Power factor	0.95
Input	
Voltage type	DC
Nominal voltage	27.0 - 36.0 V
Installation	
Height/depth	36 mm
Built-in width	595 mm
Built-in height/depth	36 mm
Length	600 mm
Built-in length	595 mm

28.03.2024
Subject to changes and printing errors

Width	600 mm
Conductor cross section	0.35 mm ²
Connection type	Push-in clamp
Suitable for suspended mounting	Yes
Number of poles	3
Suitable for built-in mounting	Yes
Suitable for surface mounting	Yes
Type of wiring	Suitable for through wiring
Suitable for ceiling mounting	Yes
D-Pak	
D-pack length	615 mm
D-pack weight	2350 g
D-pack height/diameter	45 mm
D-pack quantity	1 pcs
D-pack width	617 mm
F-Pak	
F-pack width	595 mm
F-pack height	35 mm
F-pack weight	1860 g
F-pack length	595 mm
General data	
Type of grid	Matt
M-Pak	
M-pack weight	14750 g
M-pack height	300 mm
M-pack width	646 mm
M-pack length	630 mm
Number	5
EPREL Data	
EPREL Energy Class	D