

# SLC LED DRIVER DALI2 CC DIP350-1500MA MAX 50W QA



Dali2 CC Driver fro Focus and Think panels, delivered with a quick connector that fits SLC Focus and SLC Think panels.

Technical data	
Product ID	S32201
Number of DALI-address	1
DALI-bus power consumption	2 mA
CE	Yes
Exterior color	Black
Operating temperature	-20°C ~ +45°C °C
Protection class	II
Housing	Plastic housing
Degree of protection (IP)	IP20
Suitable for constant current	Yes
Suitable for constant voltage	No
Dimming 0-10 V	No
Dimming 1-10 V	No
Dimming DALI	Yes
Dimming DMX	No
Dimming potentiometer (integrated)	No
Dimming LineSwitch	No
Dimming manufacturer's proprietary system	No
Dimming mains voltage modulation	No
Dimming phase cut-off	No
Dimming phase cut-on	No
Dimming programmable	No
Dimming RF	No
Dimming Sine Wave Reduction	No
Dimming Touch and Dim	No
Dimming Zigbee	No
Dimming with push-button	Yes
No dim function	No
Dimming DSI	No
Dimming interface	DALI DT6
Input	
Electrical connection (Input)	L`N screw connection
Power factor	0.93



01.05.2024

Subject to changes and printing errors

Suitable for DC-voltage (primary side)	No
Output	
Output power	2.0 - 50.0 W
Output voltage	8.0 - 52.0 V
Output current	350.0 - 1500.0 mA
Installation	
Length	210 mm
Height	32 mm
Width	50 mm
Model	Dynamic
Suitable for outdoor use	No
logistics data	
Brand	SLC
D-Pak	
D-pack length	380 mm
D-pack weight	15500 g
D-pack height/diameter	280 mm
D-pack quantity	50 pcs
D-pack width	270 mm
F-Pak	
F-pack width	50 mm
F-pack height	32 mm
F-pack weight	280 g
F-pack length	210 mm
M-Pak	
M-pack weight	290 g
M-pack height	54 mm
M-pack width	40 mm
M-pack length	222 mm
Number	1