



SLC SMARTONE ZIGBEE CONTROLLER CV 1X10A 12-36V MONO



Technical data	
Product ID	S24020
CE	Yes
Exterior color	White
Dimming curve (LED)	Logarithmic
Dimming range	0-100% %
ENEC	Yes
Flicker free	Yes
Operating temperature	-20°C ~ +45°C °C
Expected lifetime (Ta 25°C)	100000 Hours
Expected lifetime (Ta 45°C)	50000 Hours
Over temperature protection	Yes
Over voltage protection	Yes
RoHs	Yes
SELV	Yes
Short circuit protection	Yes
Protection class	II
Housing	Plastic housing
Programmable	Yes
Degree of protection (IP)	IP20
Number of colour channels	1
Operating method	Network
Dimming method	Pulse Width Modulation (PWM)
Dimming interface	Zigbee
Input	
Input voltage	12 - 36 V
Output	
Output type	Constant voltage (CV)
Mono	Yes
Max. output current	10 A
Output voltage	12 - 36 V
Max output current	20 A
Installation	
Length	95 mm



21.10.2020

Subject to changes and printing errors

Height	20 mm
Width	37 mm
Model	Static
Built-in	Yes
Surface-mounted	Yes
logistics data	
Brand	SLC
Imported by	The Light Group