



# SLC DESIGN CUP DOWNLIGHT R62 TED

Are you looking for something special? SLC Design Cup downlight has distinctiveness and character that will withstand time and trends passing by. SLC Design can also be tilted and rotated in the desired direction. Black: RAL9005 / White: RAL9016. System power inc.driver: 10,46W L90B20

Light technic	
Product ID	B_3234530
Beam angle	36 °, Medium beam 21-40° °
Colour rendering index (CRI/Ra)	90
Lamp efficacy	72.22 lm/W
Reflector	High-gloss
Colour rendering index CRI	90-100
Lamp type	LED not exchangeable
Light outlet	Direct
Light sharing	Symmetric
With light source	Yes
Colour of light	White
Rated life time L90/B10 at 25 °C	50000 Hours
Colour consistency (McAdam ellipse)	SDCM3
Light distributor	Reflector
Luminaire efficacy	72.22 lm/W
Energy efficiency class of the built-in lamp	A++, A+, A (LED)
Technical data	
CE	Yes
RoHs	Yes
SELV	Yes
Protection class	II
Surface protection	Powder coating
Type of control gear	LED operating device current-controlled
Material housing	Aluminium
Material cover	Plastic, transparent
Degree of protection (IP)	IP20
Control gear included	Yes
Max. system power	9 W
Adjustability	Rotating and swivelling
Rated ambient temperature according	-10 - 45 °C



18.01.2021

Subject to changes and printing errors

to IEC62722-2-1	
Dimming phase cut-off	Yes
Power factor	0.95
Dimming method	Trailing edge
Input	
Nominal voltage	220 - 230 V
Voltage type	AC/DC
Output	
LED nominal current at constant current	180 - 180 mA
Installation	
Cut-out hole (Ø)	62 mm
Height/depth	103 mm
Built-in width	62 mm
Built-in height/depth	43 mm
Length	61 mm
Built-in length	62 mm
Width	61 mm
Conductor cross section	0.35 mm <sup>2</sup>
Connection type	Plug clamp
Built-in diameter	62 mm
Suitable for suspended mounting	No
Number of poles	3
Suitable for wall mounting	Yes
Suitable for built-in mounting	Yes
Connectable conductor cross section	0.25 - 1.5 mm <sup>2</sup>
Type of wiring	Suitable for through wiring
Suitable for ceiling mounting	Yes
logistics data	
Brand	SLC
Imported by	The Light Group