



## SLC MINIONE FIXED DOWNLIGHT R25

MiniOne Fixed is a stylish mini-downlight with high lumen output and a wide beam angle designed for decorative lighting. Get the Final touch on your project with SLC MiniOne. Connect up to 6 downlights on one driver. Can be built-in or mounted on top with the MiniOne Tube accessory. Cut out hole: 25 mm / Built-in height: 18 mm.

| Light technic                                  |   |
|--|---|
| Product ID                                     | B_SLC1204                               |
| Beam angle                                     | 100 °, Extreme wide beam<br>>80° °      |
| Colour rendering index CRI                     | 90-100                                  |
| Lamp type                                      | LED not exchangeable                    |
| Light outlet                                   | Direct                                  |
| Light sharing                                  | Symmetric                               |
| With light source                              | Yes                                     |
| Rated luminous flux according to IEC 62722-2-1 | 165 lm                                  |
| Colour of light                                | White                                   |
| Rated life time L90/B10 at 25 °C               | 50000 Hours                             |
| Colour consistency (McAdam ellipse)            | SDCM3                                   |
| Light distributor                              | None                                    |
| Luminaire efficacy                             | 55 lm/W                                 |
| Energy efficiency class of the built-in lamp   | A++, A+, A (LED)                        |
| Technical data                                 |   |
| Dimmable                                       | Yes                                     |
| Protection class                               | III                                     |
| Surface protection                             | Powder coating                          |
| Type of control gear                           | LED operating device current-controlled |
| Material housing                               | Aluminium                               |
| Material cover                                 | Other                                   |
| Degree of protection (IP)                      | IP44                                    |
| Control gear included                          | No                                      |
| Max. system power                              | 3 W                                     |
| Adjustability                                  | Not adjustable                          |
| Dimming phase cut-off                          | Yes                                     |
| Dimming depending on control gear              | Yes                                     |
| Dimming method                                 | Trailing edge                           |
| Input  |   |



15.01.2021

Subject to changes and printing errors

|  |                             |
|--|-----------------------------|
| <b>Nominal voltage</b>                         | 3 - 18 V                    |
| <b>Voltage type</b>                            | DC                          |
| <b>Output</b>                                  |                             |
| <b>LED nominal current at constant current</b> | 700 - 700 mA                |
| <b>Installation</b>                            |                             |
| <b>Height/depth</b>                            | 18 mm                       |
| <b>Built-in height/depth</b>                   | 16 mm                       |
| <b>Outer diameter</b>                          | 32 mm                       |
| <b>Conductor cross section</b>                 | 0.35 mm <sup>2</sup>        |
| <b>Connection type</b>                         | Plug clamp                  |
| <b>Built-in diameter</b>                       | 25 mm                       |
| <b>Number of poles</b>                         | 2                           |
| <b>Suitable for built-in mounting</b>          | Yes                         |
| <b>Suitable for surface mounting</b>           | Yes                         |
| <b>Type of wiring</b>                          | Suitable for through wiring |
| <b>Suitable for ceiling mounting</b>           | Yes                         |
| <b>General data</b>                            |                             |
| <b>F-pack length</b>                           | 80 mm                       |