

SLC LED STRIP MAINS 120 25M 16,5 MM 8W 800LM 2700K CRI80 IP65



The LED strip is connected directly to 230V and therefore does not need a driver. Can also be dimmed with a phase-section dimmer. Time-saving and efficient solution. Supplied with a pre-fitted plug at one end. Use the end piece at the other end if the strip is cut. Can be used both indoors and outdoors. Mounting options: milled into the substrate, clip or aluminum profile. Comes in 10, 25 and 50 meter rolls.



Light technic	
Product ID	S17103
Beam angle	120 °, 120
Colour rendering index (CRI/Ra)	80
Expected lifetime	50 000
Number of LED`s per meter	80
Light reduction	L80B10
Lumens pr. meter	900 lm
MacAdam (SDCM)	3
Colour rendering index CRI	80-89
Lamp type	LED not exchangeable
Lamp power per meter	8 W/m
Number of nodes per meter	80 LED`s
Colour temperature	2700.0 - 2700.0 K
Colour of light	White
Luminous flux per meter	800 lm/m
Luminaire efficacy	100 lm/W
Technical data	
Dimmable	Yes
Max length per connection:	50 meter m
Operating temperature	-20°C ~ +45°C °C
Rated power per meter	8 W/m
Type of control gear	Not required
Suitable for dimmer	Yes
Degree of protection (IP)	IP65
Lamp voltage	220.0 - 240.0 V
Max. system power	400 W
Power factor	97
Input	
Voltage type	AC
Installation	

29.03.2024
Subject to changes and printing errors

Length of particular segments	200 mm
Height/depth	7 mm
Length	25000 mm
Width	16.5 mm
Mounting method	Surface mounting/recessed mounting
Model	Strip
Number of poles	2
With protective cover	Yes
With connection set	Yes
With end piece	Yes
Type of wiring	Ending
D-Pak	
D-pack length	390 mm
D-pack weight	4600 g
D-pack height/diameter	390 mm
D-pack quantity	1 pcs
D-pack width	130 mm
EPREL Data	
EPREL Energy Class	F
F-Pak	
F-pack height	121 mm
F-pack weight	4300 g