



SLC MINIONE TILT DOWNLIGHT R44

MiniOne Tilt is a stylish mini-downlight with high lumen output and a wide beam angle designed for decorative lighting. Get the Final touch on your project with SLC MiniOne. Assemble up to 6 downlights on a driver. The MiniOne Tilt can be tilted 40°. Cut out hole: 44 mm / Built-in height: 31 mm

Light technic	
Product ID	B_SLC1200
Beam angle	100 °, Extreme wide beam >80° °
Tilt-able	40 °
Colour rendering index CRI	90-100
Lamp type	LED not exchangeable
Light outlet	Direct
Light sharing	Symmetric
With light source	Yes
Colour temperature	2700 - 2700 K
Rated luminous flux according to IEC 62722-2-1	165 lm
Colour of light	White
Rated life time L90/B10 at 25 °C	50000 Hours
Light distributor	None
Energy efficiency class of the built-in lamp	A++, A+, A (LED)
Technical data	
Protection class	III
Surface protection	Powder coating
Type of control gear	LED operating device current-controlled
Material housing	Aluminium
Material cover	Other
Degree of protection (IP)	IP44
Max. system power	3 W
Adjustability	Swivelling
Dimming phase cut-off	Yes
Dimming depending on control gear	Yes
Dimming method	Trailing edge
Input	
Nominal voltage	3 - 18 V
Voltage type	DC
Output	



15.01.2021

Subject to changes and printing errors

LED nominal current at constant current	700 - 700 mA
Installation	
Height/depth	31 mm
Built-in height/depth	29 mm
Outer diameter	50 mm
Connection type	Plug clamp
Built-in diameter	44 mm
Number of poles	2
Suitable for built-in mounting	Yes
Type of wiring	Suitable for through wiring
Suitable for ceiling mounting	Yes
General data	
F-pack length	60 mm