

SLC MINIONE TILT DOWNLIGHT R44



SLC MiniOne Tilt is a stylish and tiltable mini-downlight with high lumen output and a wide beam angle designed for decorative lighting. Get the final touch on your project with SLC MiniOne. Connect up to 6 downlights on one driver. The MiniOne Tilt can be tilted 40°. For built-in mounting. IP44 (Front) / IP21 (Back).

Light technic	
Product ID	B_SLC1200
Beam angle	100 °, Extreme wide beam >80° °
Colour rendering index CRI	90-100
Lamp type	LED not exchangeable
Light outlet	Direct
Light sharing	Symmetric
With light source	Yes
Colour temperature	2700.0 - 2700.0 K
Rated luminous flux according to IEC 62722-2-1	165 lm
Colour of light	White
Light distributor	None
Technical data	
Protection class	III
Surface protection	Powder coating
Type of control gear	LED operating device current-controlled
Material housing	Aluminium
Material cover	Other
Degree of protection (IP)	IP44
Max. system power	3 W
Adjustability	Swivelling
Dimming phase cut-off	Yes
Input	
Voltage type	DC
Nominal voltage	3.0 - 18.0 V
Installation	
Height/depth	31 mm
Built-in height/depth	29 mm
Outer diameter	50 mm
Connection type	Push-in clamp
Number of poles	2



Suitable for built-in mounting	Yes
Type of wiring	Suitable for through wiring
Suitable for ceiling mounting	Yes
F-Pak	
F-pack width	80 mm
F-pack height	57 mm
F-pack length	60 mm