

# SLC MINIONE TILT R44 WH 3000K

## CRI90 IP44 100°



SLC MiniOne Tilt is a stylish and tiltable mini-downlight with high lumen output and a wide beam angle designed for decorative lighting. Get the final touch on your project with SLC MiniOne. Connect up to 6 downlights on one driver. The MiniOne Tilt can be tilted 40°. For built-in mounting. IP44 (Front) / IP21 (Back).



Light technic	
Product ID	SLC1202
Beam angle	100 °, Extreme wide beam >80° °
Expected lifetime	50 000
Light reduction	L90B10
Efficacy	55 lm/W
Luminous flux (lm)	165
Colour rendering index CRI	90-100
Lamp type	LED not exchangeable
Light outlet	Direct
Light sharing	Symmetric
With light source	Yes
Colour temperature	3000.0 - 3000.0 K
Rated luminous flux according to IEC 62722-2-1	165 lm
Colour of light	White
Light distributor	None
Technical data	
Protection class	III
Colour housing	White
Surface protection	Powder coating
Type of control gear	LED operating device current-controlled
Material housing	Aluminium
Material cover	Other
Degree of protection (IP)	IP44
Max. system power	3 W
Adjustability	Swivelling
Dimming phase cut-off	Yes
Input	
Voltage type	DC
Nominal voltage	3.0 - 18.0 V

26.04.2024  
Subject to changes and printing errors

Installation	
Height/depth	31 mm
Built-in height/depth	29 mm
Outer diameter	50 mm
Connection type	Push-in clamp
Number of poles	2
Suitable for built-in mounting	Yes
Type of wiring	Suitable for through wiring
Suitable for ceiling mounting	Yes
F-Pak	
F-pack width	80 mm
F-pack height	57 mm
F-pack length	60 mm
EPREL Data	
EPREL Energy Class	G
General data	
Rated power	3 W