



SLC MINIONE DRIVER 700MA 12W 9-18VDC

Driver for SLC MiniOne Downlights. Minimum three and a maximum of six downlights. Works with both the SLC MiniOne Tilt and the SLC MiniOne Fixed downlights. Splitter for three to six downlights is included.



Technical data	
Product ID	SLC1210
CE	Yes
Exterior color	White
Operating temperature	-20°C ~ +45°C °C
Expected lifetime (Ta 25°C)	50000 Hours
Over voltage protection	Yes
Short circuit protection	Yes
Tc	80 °C
Protection class	II
Housing	Plastic housing
Degree of protection (IP)	IP20
Suitable for constant current	Yes
Dimming phase cut-off	Yes
Dimming method	Trailing edge
Dimming interface	Trailing edge
Input	
Power factor	0.95
Frequency range	[50,60] Hz
Inrush Current	5 A
Input voltage	[220,240] V
Output	
Output current	700 - 700 mA
Output power	6.3 - 12.6 W
Output type	Constant current (CC)
Mono	Yes
Output voltage	9 - 18 V
Installation	
Length	109 mm
Height	22 mm
Width	40 mm
Model	Static
logistics data	

15.01.2021

Subject to changes and printing errors

Brand	SLC
Imported by	The Light Group
General data	
F-pack length	115 mm

15.01.2021

Subject to changes and printing errors