

SLC DL04 SURFACE X1 TED



The SLC DL04 Surface X1 is a square, tiltable and rotatable surface-mounted luminaire with a modern design. Bring a stylish yet timeless look to rooms where recessing into the ceiling is impossible. The excellent glare control (UGR<22) ensures a pleasant lighting experience.

Light technic	
Product ID	B_SLC1220
Beam angle	36 °, Medium beam 21-40° °
MacAdam (SDCM)	3
Glare (UGR)	UGR<22
Reflector	High-gloss
Colour rendering index CRI	90-100
Lamp type	LED not exchangeable
Light outlet	Direct
Light sharing	Symmetric
With light source	Yes
Colour of light	White
Colour consistency (McAdam ellipse)	SDCM3
Light distributor	Reflector
Technical data	
CE	Yes
Operating temperature	-20°C ~ +45°C °C
Protection class	I
Material housing	Aluminium
Material cover	Plastic, transparent
Degree of protection (IP)	IP21
Control gear included	Yes
Max. system power	8 W
Adjustability	Rotating and swivelling
Rated ambient temperature according to IEC62722-2-1	-20.0 - 45.0 °C
Dimming phase cut-off	Yes
Dimming interface	Trailing edge
Input	
Electrical connection (Input)	L`L`N`N quick connection
Voltage type	AC
Nominal voltage	220.0 - 240.0 V



Installation	
Height/depth	60 mm
Length	135 mm
Width	135 mm
Conductor cross section	0.35 mm ²
Connection type	Push-in clamp
Number of poles	2
Suitable for surface mounting	Yes
Connectable conductor cross section	1.5 - 2.5 mm ²
Type of wiring	Suitable for through wiring
Suitable for ceiling mounting	Yes
logistics data	
Imported by	The Light Group
Brand	SLC
F-Pak	
F-pack width	145 mm
F-pack height	70 mm
F-pack length	145 mm
M-Pak	
M-pack weight	16400 g
M-pack height	410 mm
M-pack width	390 mm
M-pack length	590 mm
Number	24
General data	
Rated power	8 W