

SLC DL04 SURFACE X2 TED



The DL04 Surface X2 is a square, tiltable surface-mounted luminaire in a double version and modern design. Bring the classic LED spot look to rooms where recessing into the ceiling is not possible. The tiltable and rotatable spots, the timeless design, and the good glare control UGR<22 ensure a pleasant and flexible lighting experience.



Light technic	
Product ID	B_SLC1228
Beam angle	36 °, Medium beam 21-40° °
Glare (UGR)	UGR<22
Reflector	High-gloss
Colour rendering index CRI	90-100
Lamp type	LED not exchangeable
Light outlet	Direct
Light sharing	Symmetric
With light source	Yes
Colour of light	White
Colour consistency (McAdam ellipse)	SDCM3
Light distributor	Reflector
Technical data	
CE	Yes
Protection class	I
Surface protection	Powder coating
Type of control gear	LED operating device current-controlled
Material housing	Aluminium
Material cover	Plastic, transparent
Degree of protection (IP)	IP21
Control gear included	Yes
Max. system power	16 W
Adjustability	Swivelling
Rated ambient temperature according to IEC62722-2-1	-20.0 - 45.0 °C
Dimming phase cut-off	Yes
Input	
Voltage type	AC
Installation	
Height/depth	60 mm
Length	224 mm

28.03.2024
Subject to changes and printing errors

Width	135 mm
Type of installation	Surface
Conductor cross section	0.35 mm ²
Connection type	Push-in clamp
Number of poles	2
Suitable for surface mounting	Yes
Connectable conductor cross section	1.5 - 2.5 mm ²
Type of wiring	Suitable for through wiring
Suitable for ceiling mounting	Yes
logistics data	
Imported by	The Light Group
Brand	SLC
D-Pak	
D-pack length	310 mm
D-pack weight	13400 g
D-pack height/diameter	590 mm
D-pack quantity	12 pcs
D-pack width	400 mm
F-Pak	
F-pack width	145 mm
F-pack height	70 mm
F-pack length	234 mm