

# SLC DL04 SQUARE X2 R83 TED



The SLC DL04 Square X2 is a square, tiltable (25°) recessed luminaire in a double version. Experience pleasant light with low glare and a good colour rendering index.



Light technic	
Product ID	B_SLC1244
Beam angle	36 °, Medium beam 21-40° °
MacAdam (SDCM)	3
Glare (UGR)	UGR<22
Reflector	High-gloss
Colour rendering index CRI	90-100
Lamp type	LED not exchangeable
Light outlet	Direct
Light sharing	Symmetric
With light source	Yes
Colour of light	White
Colour consistency (McAdam ellipse)	SDCM3
Light distributor	Reflector
Technical data	
CE	Yes
Protection class	II
Surface protection	Powder coating
Type of control gear	LED operating device current-controlled
Material housing	Aluminium
Material cover	Plastic, transparent
Degree of protection (IP)	IP54
Control gear included	Yes
Max. system power	20 W
Adjustability	Swivelling
Rated ambient temperature according to IEC62722-2-1	-20.0 - 45.0 °C
Dimming phase cut-off	Yes
Dimming interface	Trailing edge
Input	
Power factor	0.95
Voltage type	AC
Nominal voltage	220.0 - 240.0 V
Installation	

25.04.2024  
Subject to changes and printing errors

Height/depth	56.4 mm
Built-in width	183.5 mm
Height	56.4 mm
Built-in height/depth	56 mm
Length	95 mm, 95 mm
Built-in length	83 mm
Width	190 mm, 190 mm
Type of installation	Recessed
Conductor cross section	0.35 mm <sup>2</sup>
Connection type	Push-in clamp
Number of poles	2
Suitable for built-in mounting	Yes
Connectable conductor cross section	1.5 - 2.5 mm <sup>2</sup>
Type of wiring	Suitable for through wiring
Suitable for ceiling mounting	Yes
logistics data	
Imported by	The Light Group
Brand	SLC
General data	
Rated power	20 W