



SLC ONE360 SUNLIKE DOWNLIGHT

R68-83

With the SLC One360° SunLike recessed luminaires, we bring natural, sun-like light into interiors - less blue spectrum for healthier light and more well-being. The successful One360° has been expanded with our new One360° SunLike product. Equipped with SunLike chip technology. Supplied completely ready for connection with driver in environmentally friendly packaging.

Light technic	
Product ID	B_SLC1160
Beam angle	36 °, Medium beam 21-40° °
MacAdam (SDCM)	3
Reflector	High-gloss
Colour rendering index CRI	90-100
Lamp type	LED not exchangeable
Light outlet	Direct
Light sharing	Symmetric
With light source	Yes
Colour of light	White
Colour consistency (MacAdam ellipse)	SDCM3
Light distributor	Reflector
Luminaire efficacy	75 lm/W
Technical data	
IP class	IP44
Operating temperature	-10°C ~ +45°C °C
Protection class	II
Surface protection	Powder coating
Type of control gear	LED operating device current-controlled
Material housing	Aluminium
Material cover	Plastic, transparent
Degree of protection (IP)	IP44
Control gear included	Yes
Max. system power	8 W
Adjustability	Rotating and swivelling
Rated ambient temperature according to IEC62722-2-1	-10.0 - 45.0 °C
Dimming phase cut-off	Yes
Power factor	0.9
Input	



SunLike

Electrical connection (Input)	L`L`N`N quick connection
Voltage type	AC
Nominal voltage	220.0 - 240.0 V
Installation	
Built-in width	67 mm
Height	45.4 mm
Built-in height/depth	46 mm
Length	90 mm
Width	90 mm
Can be installed directly into the insulation	Yes
Type of installation	Recessed
Outer diameter	90 mm
Conductor cross section	0.35 mm ²
Connection type	Push-in clamp
Suitable for suspended mounting	No
Number of poles	3
Suitable for built-in mounting	Yes
Connectable conductor cross section	0.75 - 2.5 mm ²
Type of wiring	Suitable for through wiring
Suitable for ceiling mounting	Yes
logistics data	
Imported by	The Light Group
Brand	SLC
F-Pak	
F-pack width	112 mm
F-pack height	100 mm
F-pack weight	365 g
F-pack length	100 mm
M-Pak	
M-pack weight	19200 g
M-pack height	520 mm
M-pack width	232 mm
M-pack length	535 mm
Number	50
General data	
Pallet length	1200 mm